


SHP-T Standard MEA SHP-T 250W 0024017





PRODUCT OVERVIEW

MEA SHP-T 250W
HID
250
SHP-T
E40
Clear
Logistics & Industry
EC000821
28000
2000
20
250
No
28000
5410288240176

DATA TABLE

General data	
Product name	MEA SHP-T 250W
Technology	HID
Watt (Rated) (W)	250
Туре	SHP-T
Cap/Base	E40
Lamp finish	Clear
General application	Logistics & Industry
ETIM Class	EC000821
Optical data	
Luminous flux (Im)	28000
Luminous flux (Rated) (Im)	28000
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	2000

SYLVANIA

SHP-T Standard MEA SHP-T 250W 0024017

CRI (Ra)	20
Adjustable chromaticity	Ν
Rated lumen maint. factor (%) at 4000 h 50Hz	96
Rated lumen maint. factor (%) at 6000 h 50Hz	95
Rated lumen maint. factor (%) at 8000 h 50Hz	93
Rated lumen maint. factor (%) at 12000 h 50Hz	90
Rated lumen maint. factor (%) at 16000 h 50Hz	88
Rated lumen maint. factor (%) at 20000 h 50Hz	86
Electrical data	
Wattage (W)	250
Control gear required	Yes
Transformer required	No
Dimmable	No
Lamp Energy Label (class)	F
kWh per 1000 hours burning time	275
Lifetime data	
Average life (Nominal) (h)	28000
Average life (Rated) (h)	28000
Rated survival factor (%) at 2000 h 50Hz	99
Rated survival factor (%) at 4000 h 50Hz	97
Rated survival factor (%) at 6000 h 50Hz	95
Rated survival factor (%) at 8000 h 50Hz	92
Rated survival factor (%) at 12000 h 50Hz	88
Rated survival factor (%) at 16000 h 50Hz	83
Rated survival factor (%) at 20000 h 50Hz	78
Physical data	
Nominal Product Diameter (mm)	47
Max. Lamp Diameter (mm) - D	47
	0.217
Weight (kg)	0.217
Packaging	
Single packaging type	Carton
Product EAN number	5410288240176
Packaging single length / height (cm)	29.9
Packaging single width (cm)	4.7
Packaging single depth (cm)	4.7
Units per outer package	12
Packaging outer length / height (cm)	30.4
Packaging outer width (cm)	15.6



SHP-T Standard MEA SHP-T 250W 0024017

Packaging outer depth (cm)	20.8
Safety data	
Lamp mercury content (mg)	8
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Suitable for household illumination	No