



MASTER TL5 High Output



MASTER TL5 HO 24W/840 SLV/40

This TL5 lamp (tube diameter 16 mm) offers high light output. The TL5 HO lamp is optimized for installations requiring high light output and offers excellent lumen maintenance and color rendering. Application areas vary from offices and industry to schools and retail environments.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information			
Cap-Base	G5		
Features	na [Not Applicable]		
Flux measurement reference	Sphere		
Light Technical			
Color Code	840 [CCT of 4000K]		
Luminous Flux	1,700 lm		
Color Designation	Cool White (CW)		
Chromaticity Coordinate X (Nom)	0.38		
Chromaticity Coordinate Y (Nom)	0.38		
Correlated Color Temperature (Nom)	4000 K		
Luminous Efficacy (rated) (Nom)	76 lm/W		
Color rendering index (CRI)	82		

Operating and Electrical	
Power Consumption	22.7 W
Lamp Current (Nom)	0.295 A
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Shape	T5
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Nom)	1.2 mg
Energy Consumption kWh/1000 h	23 kWh
EPREL Registration Number	423555


Datasheet, 2024, March 4 data subject to change

MASTER TL5 High Output

Product Data	
Order product name	MASTER TL5 HO 24W/840 SLV/40
Full product name	MASTER TL5 HO 24W/840 SLV/40
Full product code	871150063960855
Order code	927928084055
Material Nr. (12NC)	927928084055


Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500639608
Numerator - Packs per outer box	40
EAN/UPC - Case	8711500867841

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HO 24W/840	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm
SLV/40					


Photometric data



Spectral Power Distribution Colour - MASTER TL5 HO 24W/840 SLV/40

Lifetime





Life Expectancy Diagram - MASTER TL5 HO 24W/840 SLV/40

Lumen Maintenance Diagram - MASTER TL5 HO 24W/840 SLV/40

MASTER TL5 High Output

Lifetime

Life Expectancy Diagram - MASTER TL5 HO 24W/840 SLV/40



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.